

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (Currently amended) Retaining clip for, in particular, simultaneous fastening of a plurality of approximately parallel-running, elongate articles to a structure, in particular for the fastening of lines, pipes or cables, having a base part, in which receivers for the elongate articles are formed, having at least one partition between two such receivers, which comprises a front side and a rear side, wherein there are provided for securing the elongate articles in the receivers at least one first latching finger at the front side and at least one second latching finger at the rear side of the partition, ~~characterised~~ characterized in that the width of each latching finger is smaller than the width of the partition and the first latching finger is arranged offset relative to the second latching finger in such a way that no overlapping occurs, wherein an elbow is disposed between the first and second latching fingers.

2. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized in that the first latching finger is arranged laterally offset relative to the second latching finger at a distance of 5 to 20% of the width of the partition.

3. Cancelled

4. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized in that the partition has an opening in the form of a slot.

5. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized in that on both sides of the partition two or more vertically offset latching fingers are disposed respectively.

6. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized in that the ratio of the width of an individual latching finger to the width of the partition is between 1:4 and 1:2.

7. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized by outer walls, which for securing the elongate articles have at least one latching finger.

8. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized by outer walls, which are reinforced by reinforcing structures.

9. (Currently amended) Retaining clip according to claim 1, ~~characterised~~ characterized in that the retaining clip is made of elastic plastics material.

10. (Currently amended) Retaining clip according to claim 1, characterised characterized in that the first latching finger is arranged laterally offset relative to the second latching finger at a distance of 10 to 15% of the width of the partition.

11. (Currently amended) Retaining clip according to claim 1, characterised characterized in that the ratio of the width of an individual latching finger to the width of the partition is approximately 2:5.

12. (New) Retaining clip for, in particular, simultaneous fastening of a plurality of approximately parallel-running, elongate articles to a structure comprising:

a base part, defining a plurality of receivers for the elongate articles, each receiver having at least one partition between two such receivers, each partition having a front and a rear side and having at least one first pair of latching fingers at the front side and at least one pair of second latching fingers at the rear side of the partition,;

wherein the width of each latching finger is smaller than the width of the partition and the first pair of latching fingers are arranged offset relative to the second pair of latching fingers in such a way that no overlapping occurs and wherein the first pair of latching fingers are arranged laterally offset relative to the second pair of latching fingers at a distance of 5 to 20% of the width of the partition.

13. (New) A retaining clip according to Claim 12, wherein the each partition is elbowed between the offset latching fingers.

14. (New) A retaining clip according to Claim 12, wherein the partition has an opening in the form of a slot.

15. (New) A retaining clip according to Claim 12, wherein both sides of the partition two or more vertically offset latching fingers are disposed respectively.

16. (New) A retaining clip according to Claim 12, wherein the ratio of the width of an individual latching finger to the width of the partition is between 1:4 and 1:2.

17. (New) A retaining clip according to Claim 12, wherein the outer walls, which for securing the elongate articles have at least one latching finger.